

Description	Part #	Size Usage Range		Maximum Allowable Back Pressure PSI and Feet of Head	Required Inflation Pressure	Weight	Deflated Diameter	Deflated Length	Inflation Fitting	Eye Bolts Size & Quantity
		Minimum Diameter	Maximum Diameter							
3-4" FatBoy Plugster™	200-34	2.9" 75mm	4.3" 109mm	20 PSI 46 FT	35 PSI	0.66 LBS	2.75"	6"	1/8" Tank Valve Removable	1/4" (1)
4" - 6" FatBoy Plugster™	200-46	3.75" 100mm	6.4" 162mm	17 PSI 39 FT	45 PSI	1.5 LBS	3.5"	9"	1/8" Tank Valve Removable	1/4" (1)
6"-10" FatBoy Plugster™	200-610	5.5" 150mm	10.58" 268mm	13 PSI 30 FT	30 PSI	4.5 LBS	5.2"	17.25"	1/4" Tank Valve Removable	3/8" (1) & (1) Optional 3/8" Backside Eyebolt
8"-12" FatBoy Plugster™	200-812	7" 200mm	12.64" 321mm	13 PSI 30 FT	25 PSI	6.75 LBS	6.75"	19"	1/4" Tank Valve Removable	3/8" (1) & (1) Optional 3/8" Backside Eyebolt
12"-18" FatBoy Plugster™	200-1218	11" 200mm	18.50" 479mm	13 PSI 30 FT	25 PSI	24 LBS	10.75"	28"	1/4" Tank Valve Removable	3/8" (2) & (1) Optional 3/8" Backside Eyebolt
12"-24" FatBoy Plugster™	200-1224	11" 300mm	24.5" 600mm	13 PSI 30 FT	30 PSI	27 lbs	10.75"	37"	1/4" Tank Valve Removable	3/8" (2) & (1) Optional 3/8" Backside Eyebolt
12"-24" FatBoy Plugster™ With Max-Guard™ (Relief Valve)	200-1224MG	11" 300mm	24.5" 600mm	13 PSI 30 Ft	30 PSI	28	10.75"	37"	1/4" Quick Disconnect Nipple (removable)	3/8" (2) (1) Optional 3/8" Backside Eyebolt
12"-24" FatBoy Plugster™ With Max-Guard™ (Relief Valve) Max-Sleeve™ Installed	200-1224 MGMS	11" 300mm	24.5" 600mm	13 PSI 30 Ft	30 PSI	41	10.75"	37"	1/4" Quick Disconnect Nipple (removable)	3/8" (2) (1) Optional 3/8" Backside Eyebolt
15"-30" FatBoy Plugster™	200-1530	14" 375 mm	31.5" 800mm	11 PSI 25 FT	25 Psi	50 lbs	13.75"	50"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
15"-30" FatBoy Plugster™ With Max-Guard™ (Relief Valve)	200-1530MG	14" 375 mm	31.5" 800mm	11 PSI 25 FT	25 Psi	50 lbs	13.75"	50"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
15"-30" FatBoy Plugster™ With Max-Sleeve™ Installed	200-1530MS	14" 375 mm	31.5" 800mm	11 PSI 25 FT	25 Psi	71 lbs	13.75"	50"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
15"-30" FatBoy Plugster™ With Max-Guard™ (Relief valve) and Max-Sleeve™ Installed	200-1530 MGMS	14" 375 mm	31.5" 800mm	11 PSI 25 FT	25 Psi	71 lbs	13.75"	50"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
18"-36" FatBoy Plugster	200-1836	16.5" 420mm	37.5" 950mm	11 PSI 25 FT	25 PSI	68 lbs	16"	60"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
18"-36" FatBoy Plugster™ With Max-Guard™ (Relief Valve)	200-1836MG	16.5" 420mm	37.5" 950mm	11 PSI 25 FT	25 PSI	68 lbs	16"	60"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
18"-36" FatBoy Plugster™ With Max-Sleeve™ Installed	200-1836MS	16.5" 420mm	37.5" 950mm	11 PSI 25 FT	25 PSI	95 lbs	16"	60"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
18"-36" FatBoy Plugster™ With Max-Guard™ (Relief valve) and Max-Sleeve™ Installed	200-1836 MGMS	16.5" 420mm	37.5" 950mm	11 PSI 25 FT	25 PSI	95 lbs	16"	60"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
24"-48" FatBoy Plugster™	200-2448	22" 610 mm	49.5" 1,220mm	11 PSI 25 FT	25 PSI	120 lbs	21"	76"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
24"-48" FatBoy Plugster™ With Max-Guard™ (Relief Valve)	200-2448MG	22" 610 mm	49.5" 1,220mm	11 PSI 25 FT	25 Psi	120 lbs	21"	76"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
24"-48" FatBoy Plugster™ With Max-Sleeve™ Installed	200-2448MS	22" 610 mm	49.5" 1,220mm	11 PSI 25 FT	25 PSI	170 lbs	21"	76"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
24"-48" FatBoy Plugster™ With Max-Guard™ (Relief valve) and Max-Sleeve™ Installed	200-2448 MGMS	22" 610 mm	49.5" 1,220mm	11 PSI 25 FT	25 Psi	170 lbs	21"	76"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside