

Description	Part #	Size Usage Range		Maximum Allowable Back Pressure PSI and Feet of Head	Required Inflation Pressure	Weight	Deflated Diameter	Deflated Length	Inflation Fitting	Eye Bolts Size & Quantity	Bypass Size (s)
		Minimum Diameter	Maximum Diameter								
3"-4" FatBoy Guzzler™ with 1/4" Bypass	250-34	2.75" 70mm	4.3" 109mm	20 PSI 46 FT	35 PSI	.75 LBS	2.65"	6.25"	1/8" Tank Valve (removable) and QD Nipple	(1) 1/4"	1/4" NPT (F)
4" - 6" FatBoy Guzzler™ with 3/4" Bypass	250-46	3.75" 95mm	6.4" 162mm	17 PSI 39 FT	45 PSI	2.25 lbs	3.5"	9"	1/8" Tank Valve (removable) and QD Nipple	(1) 1/4"	3/4" NPT (F)
6"-10" FatBoy Guzzler™ with 2" Bypass	250-610	5.5" 140mm	10.5" 266mm	13 PSI 30 FT	30 PSI	7 lbs	5.25"	17.5"	1/8" Tank Valve (removable) and QD Nipple	(1) 1/4"	2" NPT (F)
6"-10" Max-Guzzler™ with 4" Bypass	274-610	5.75" 146mm	10.5" 250mm	10 PSI 23 FT	35 PSI	13 Lbs	5.6"	23"	1/4" QD Nipple (removable)	1/4" x 1-1/8" Galvanized Shackles	4" (M) NPT
8"-12" FatBoy Guzzler™ with 3" Bypass	250-812	7" 177mm	12.64" 321mm	13 PSI 30 FT	25 PSI	11.5 lbs	6.75"	19"	1/4" QD Nipple (removable)	(1) 3/8"	3" NPT (F)
8"-12" Max-Guzzler™ with 4" Bypass	274-812	7" 177mm	12.64" 321mm	10 PSI 23 FT	45 PSI	20 LBS	6.5"	26.5"	1/4" QD Nipple (removable)	1/4" x 1-1/8" Galvanized Shackles	4" (M) NPT
8"-12" Max-Guzzler™ with 6" Bypass	276-812	7.75" 321mm	12.64" 321mm	10 PSI 23 FT	35 PSI	20 Lbs	7.5"	25"	1/4" QD Nipple (removable)	1/4" x 1-1/8" Galvanized Shackles	6" (M) NPT
12"-18" FatBoy Guzzler™ with 4" Bypass	274-1218	10.75" 300mm	18.5" 450mm	10 PSI 23 FT	35 PSI	47 lbs	10.5"	32"	1/4" QD Nipple (removable)	1/4" x 1-1/8" Galvanized Shackles	4" (M) NPT
12"-18" Max-Guzzler™ with 6" Bypass	276-1218	10" 254mm	18.5" 470mm	10 PSI 23 FT	35 PSI	48 lbs	9.5"	30.75"	1/4" QD Nipple (removable)	1/4" x 1-1/8" Galvanized Shackles	6" (M) NPT
12"-18" Max-Guzzler™ with 8" Bypass (No Cap)	278-1218	10" 254mm	18.5" 470mm	10 PSI 23 FT	35 PSI	48 lbs	9.5"	31"	1/4" QD Nipple (removable)	1/4" x 1-1/8" Galvanized Shackles	8" (M) NPT**
12"-24" Max-Guzzler™ with 4" Bypass	274-1224	10" 254mm	24.5" 622mm	5 PSI 11.5 FT	45 PSI	59 lbs	9.5"	42.5"	1/4" QD Nipple (removable)	1/4" x 1-1/8" Galvanized Shackles	4" (M) NPT
12"-24" Max-Guzzler™ with 6" Bypass	276-1224	10" 254mm	24.5" 622mm	5 PSI 11.5 FT	45 PSI	61 lbs	9.5"	42.5"	1/4" QD Nipple (removable)	1/4" x 1-1/8" Galvanized Shackles	6" (M) NPT
12"-24" Max-Guzzler™ with 8" Bypass (No Cap)	278-1224	10" 254mm	24.5" 622mm	5 PSI 11.5 FT	45 PSI	63 lbs	9.5"	43"	1/4" QD Nipple (removable)	1/4" x 1-1/8" Galvanized Shackles	8" (M) NPT**
15"-30" FatBoy Guzzler™ with 4" Bypass	250-1530	14" 355 mm	31.5" 775mm	11 PSI 25Ft	25 Psi	68 lbs	14"	58"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
15"-30" FatBoy Guzzler™ with 4" Bypass and Max-Guard™ (Relief Valve™)	250-1530 MG	14" 355 mm	31.5" 775mm	11 PSI 25Ft	25 Psi	68 lbs	14"	58"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
15"-30" FatBoy Guzzler™ with 4" Bypass and Max-Sleeve™ Installed	250-1530 MS	14.25" 362mm	31.5" 775mm	11 PSI 25Ft	25 Psi	90 lbs	14"	58"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
15"-30" FatBoy Guzzler™ with 4" Bypass and Max-Guard™ (Relief Valve) and Max-Sleeve™ Installed	250-1530 MGMS	14.25" 362 mm	31.5" 775mm	11 PSI 25Ft	25 Psi	90 lbs	14"	58"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
18"-36" FatBoy Guzzler™ with 4" Bypass	250-1836	16.5" 419mm	37.5" 950mm	11 PSI 25Ft	25 Psi	88 lbs	16"	65"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
18"-36" FatBoy Guzzler™ with 4" Bypass and Max-Guard™ (Relief Valve)	250-1836 MG	16.5" 419mm	37.5" 950mm	11 PSI 25Ft	25 Psi	88 lbs	16"	65"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
18"-36" FatBoy Guzzler™ with 4" Bypass and Max-Sleeve™ Installed	250-1836 MS	17" 430mm	37.5" 950mm	11 PSI 25Ft	25 Psi	118 lbs	16.5"	65"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
18"-36" FatBoy Guzzler™ with 4" Bypass and Max-Guard™ (Relief Valve) and Max-Sleeve™ Installed	250-1836 MGMS	17" 430mm	37.5" 950mm	11 PSI 25Ft	25 Psi	118 lbs	16.5"	65"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
24"-48" FatBoy Guzzler™ with 4" Bypass	250-2448	22" 558 mm	49.5" 1,220mm	11 PSI 25Ft	25 PSI	140 lbs	21"	82"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
24"-48" FatBoy Guzzler™ with 4" Bypass and Max-Guard™ (Relief Valve)	250-2448 MG	22" 558 mm	49.5" 1,257mm	11 PSI 25Ft	25 Psi	140 lbs	21"	82"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
24"-48" FatBoy Guzzler™ with 4" Bypass and Max-Sleeve™ Installed	250-2448 MS	22" 558 mm	49.5" 1,257mm	11 PSI 25Ft	25 PSI	190 lbs	21"	82"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
24"-48" FatBoy Guzzler™ with 4" Bypass and Max-Guard™ (Relief Valve) and Max-Sleeve™ Installed	250-2448 MGMS	22" 558 mm	49.5" 1,257mm	11 PSI 25Ft	25 Psi	190lbs	21"	82"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (M) NPT
24"-48" FatBoy Guzzler™ with 6" Bypass and Max-Guard™ (Relief Valve)	276-2448 MG	22" 558 mm	49.5" 1,257mm	11 PSI 25Ft	25 Psi	150 lbs	21"	82"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	6" (M) NPT
24"-48" FatBoy Guzzler™ with 6" Bypass and Max-Guard™ (Relief Valve) and Max-Sleeve™ Installed	276-2448 MGMS	22" 558 mm	49.5" 1,257mm	11 PSI 25Ft	25 Psi	200 lbs	21"	82"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	6" (M) NPT