

Description	Part #	Size Usage Range		Maximum Allowable Back Pressure PSI and Feet of Head	Required Inflation Pressure	Weight	Deflated Diameter	Deflated Length	Inflation Fitting	Eye Bolt Size & Quantity
		Minimum Diameter	Maximum Diameter							
3-4" FatBoy Plugster™	200-34	2.9" 75 mm	4.3" 109 mm	20 PSI 46 Ft	35 PSI	0.66 lbs	2.75"	6"	1/8" QD Nipple and Tank Valve (removable)	(1) 1/4" Frontside
4"-6" FatBoy Plugster™	200-46	3.75" 100 mm	6.4" 162 mm	17 PSI 39 Ft	45 PSI	1.5 lbs	3.5"	9"	1/8" QD Nipple and Tank Valve (removable)	(1) 1/4" Frontside
<b>New Size!</b> 4"-8" FatBoy Plugster™	200-48	3.75" 100 mm	8.3" 210 mm	15 PSI 35 Ft	45 PSI	2.5 lbs	3.5"	16"	1/8" QD Nipple and Tank Valve (removable)	(1) 1/4" Frontside
6"-10" FatBoy Plugster™	200-610	5.5" 150 mm	10.58" 268 mm	13 PSI 30 Ft	30 PSI	4.5 lbs	5.2"	17.25"	1/4" QD Nipple (removable)	(1) 3/8" Frontside (1) 3/8" Optional Backside
<b>New Size!</b> 6"-12" FatBoy Plugster™	200-612	5.5" 150 mm	12.30" 310 mm	11 PSI 25 Ft	35 PSI	6 lbs	5.2"	23"	1/4" QD Nipple (removable)	(1) 3/8" Frontside (1) 3/8" Optional Backside
8"-12" FatBoy Plugster™	200-812	7" 200 mm	12.64" 321 mm	13 PSI 30 Ft	25 PSI	6.75 lbs	6.75"	19"	1/4" QD Nipple (removable)	(1) 3/8" Frontside (1) 3/8" Optional Backside
12"-18" FatBoy Plugster™	200-1218	11" 200 mm	18.50" 479 mm	13 PSI 30 Ft	25 PSI	24 lbs	10.75"	28"	1/4" QD Nipple (removable)	(1) 3/8" Frontside (1) 3/8" Optional Backside
12"-18" FatBoy Plugster™ with Max-Sleeve™ Installed	200-1218MS	11" 200 mm	18.50" 479 mm	13 PSI 30 Ft	25 PSI	35 lbs	10.75"	28"	1/4" QD Nipple (removable)	(2) 3/8" Frontside (1) 3/8" Optional Backside
<b>New Optional Relief Valve!</b> 12"-18" FatBoy Plugster™ With Max-Guard™ (relief valve)	200-1218MG	11" 200 mm	18.50" 479 mm	13 PSI 30 Ft	25 PSI	24 lbs	10.75"	28"	1/4" QD Nipple (removable)	(1) 3/8" Frontside (1) 3/8" Optional Backside
<b>New Optional Relief Valve!</b> 12"-18" FatBoy Plugster™ With Max-Guard™ (relief valve) Max-Sleeve™ Installed	200-1218MGMS	11" 200 mm	18.50" 479 mm	13 PSI 30 Ft	25 PSI	35 lbs	10.75"	28"	1/4" QD Nipple (removable)	(1) 3/8" Frontside (1) 3/8" Optional Backside
12"-24" FatBoy Plugster™	200-1224	11" 300 mm	24.5" 600 mm	13 PSI 30 Ft	30 PSI	27 lbs	10.75"	37"	1/4" QD Nipple (removable)	(2) 3/8" Frontside (1) 3/8" Optional Backside
12"-24" FatBoy Plugster™ with Max-Sleeve™ Installed	200-1224MS	11" 300 mm	24.5" 600 mm	13 PSI 30 Ft	30 PSI	40 lbs	10.75"	37"	1/4" QD Nipple (removable)	(2) 3/8" Frontside (1) 3/8" Optional Backside
<b>New Optional Relief Valve!</b> 12"-24" FatBoy Plugster™ With Max-Guard™ (relief valve)	200-1224MG	11" 300 mm	24.5" 600 mm	13 PSI 30 Ft	30 PSI	28 lbs	10.75"	37"	1/4" QD Nipple (removable)	(1) 3/8" Frontside (1) 3/8" Optional Backside
<b>New Optional Relief Valve!</b> 12"-24" FatBoy Plugster™ With Max-Guard™ (relief valve) Max-Sleeve™ Installed	200-1224MGMS	11" 300 mm	24.5" 600 mm	13 PSI 30 Ft	30 PSI	41 lbs	10.75"	37"	1/4" QD Nipple (removable)	(1) 3/8" Frontside (1) 3/8" Optional Backside
15"-30" FatBoy Plugster™	200-1530	14" 375 mm	31.5" 800 mm	11 PSI 25 Ft	25 PSI	50 lbs	13.75"	50"	(1) 1/4" QD Nipple (removable)	(2) 1/2" Frontside (2) 1/2" Optional Backside
15"-30" FatBoy Plugster™ With Max-Guard™ (relief valve)	200-1530MG	14" 375 mm	31.5" 800 mm	11 PSI 25 Ft	25 PSI	50 lbs	13.75"	50"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
15"-30" FatBoy Plugster™ With Max-Sleeve™ Installed	200-1530MS	14" 375 mm	31.5" 800 mm	11 PSI 25 Ft	25 PSI	71 lbs	13.75"	50"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
15"-30" FatBoy Plugster™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed	200-1530MGMS	14" 375 mm	31.5" 800 mm	11 PSI 25 Ft	25 PSI	71 lbs	13.75"	50"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
18"-36" FatBoy Plugster	200-1836	16.5" 420 mm	37.5" 950 mm	11 PSI 25 Ft	25 PSI	68 lbs	16"	60"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
18"-36" FatBoy Plugster™ With Max-Guard™ (relief valve)	200-1836MG	16.5" 420 mm	37.5" 950 mm	11 PSI 25 Ft	25 PSI	68 lbs	16"	60"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
18"-36" FatBoy Plugster™ With Max-Sleeve™ Installed	200-1836MS	16.5" 420 mm	37.5" 950 mm	11 PSI 25 Ft	25 PSI	95 lbs	16"	60"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
18"-36" FatBoy Plugster™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed	200-1836MGMS	16.5" 420 mm	37.5" 950 mm	11 PSI 25 Ft	25 PSI	95 lbs	16"	60"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
24"-48" FatBoy Plugster™	200-2448	22" 610 mm	49.5" 1,220 mm	11 PSI 25 Ft	25 PSI	120 lbs	21"	76"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
24"-48" FatBoy Plugster™ With Max-Guard™ (relief valve)	200-2448MG	22" 610 mm	49.5" 1,220 mm	11 PSI 25 Ft	25 PSI	120 lbs	21"	76"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
24"-48" FatBoy Plugster™ With Max-Sleeve™ Installed	200-2448MS	22" 610 mm	49.5" 1,220 mm	11 PSI 25 Ft	25 PSI	170 lbs	21"	76"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
24"-48" FatBoy Plugster™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed	200-2448MGMS	22" 610 mm	49.5" 1,220 mm	11 PSI 25 Ft	25 PSI	170 lbs	21"	76"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
<b>New Size!</b> 24"-60" FatBoy Plugster™ With Max-Guard™ (relief valve)	200-2460MG	21" 550 mm	61.5" 1550 mm	9 PSI 20 Ft	25 PSI	175 lbs	20.5"	95"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside
<b>New Size!</b> 24"-60" FatBoy Plugster™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed	200-2460MGMS	21" 550 mm	61.5" 1550 mm	9 PSI 20 Ft	25 PSI	240 lbs	21"	95"	(1) 1/4" QD Nipple (removable) (1) 1/2" NTP (female) (plugged)	(2) 1/2" Frontside (2) 1/2" Optional Backside