

Description	Part #	Size Usage Range		Maximum Allowable Back Pressure PSI and Feet of Head	Required Inflation Pressure	Weight	Deflated Diameter	Deflated Length	Inflation Fitting	Eye Bolt Size & Quantity	Bypass Size (s) NPT
		Minimum Diameter	Maximum Diameter								
12"-18" FatBoy Plugster™ With Max-Guard™ (relief valve)	200-1218MG	11" 300mm	18.5" 450mm	13 PSI 30 Ft	25 PSI	31 lbs	10.75"	28"	1/4" Quick Disconnect Nipple (removable)	(2) (3/8") Frontside (1) (3/8") Backside Eyebolt Optional	No Bypass
12"-18" FatBoy Plugster™ With Max-Guard™ (relief valve) Max-Sleeve™ Installed	200-1218 MGMS	11" 300mm	18.5" 450mm	13 PSI 30 Ft	25 PSI	31 lbs	10.75"	28"	1/4" Quick Disconnect Nipple (removable)	(2) (3/8") Frontside (1) (3/8") Backside Eyebolt Optional	No Bypass
12"-18" FatBoy Tester™ With Max-Guard™ (relief valve)	225-1218MG	11" 300mm	18.5" 450mm	13 PSI 30 Ft	25 PSI	31 lbs	10.75"	28"	1/4" Quick Disconnect Nipple (removable)	(1) (3/8") Frontside (1) (3/8") Backside Eyebolt Optional	3/4" and 1/4"
12"-18" FatBoy Tester™ With Max-Guard™ (relief valve) Max-Sleeve™ Installed	225-1218 MGMS	11" 300mm	18.5" 450mm	13 PSI 30 Ft	25 PSI	31 lbs	10.75"	28"	1/4" Quick Disconnect Nipple (removable)	(1) (3/8") Frontside (1) (3/8") Backside Eyebolt Optional	3/4" and 1/4"
12"-24" FatBoy Plugster™ With Max-Guard™ (relief valve)	200-1224MG	11" 300mm	24.5" 600mm	13 PSI 30 Ft	30 PSI	28 lbs	10.75"	37"	1/4" Quick Disconnect Nipple (removable)	(1) (3/8") Frontside (1) (3/8") Backside Eyebolt Optional	No Bypass
12"-24" FatBoy Plugster™ With Max-Guard™ (relief valve) Max-Sleeve™ Installed	200-1224 MGMS	11" 300mm	24.5" 600mm	13 PSI 30 Ft	30 PSI	41 lbs	10.75"	37"	1/4" Quick Disconnect Nipple (removable)	(1) (3/8") Frontside (1) (3/8") Backside Eyebolt Optional	No Bypass
12"-24" FatBoy Tester™ With Max-Guard™ (relief valve)	225-1224MG	11" 300mm	24.5" 600mm	13 PSI 30 Ft	30 PSI	37 lbs	10.75"	37"	1/4" Quick Disconnect Nipple (removable)	(1) (3/8") Frontside (1) (3/8") Backside Eyebolt Optional	3/4" and 1/4"
12"-24" FatBoy Tester™ With Max-Guard™ (relief valve) Max-Sleeve™ Installed	225-1224 MGMS	11" 300mm	24.5" 600mm	13 PSI 30 Ft	30 PSI	50 lbs	10.75"	37"	1/4" Quick Disconnect Nipple (removable)	(1) (3/8") Frontside (1) (3/8") Backside Eyebolt Optional	3/4" and 1/4"