

Description	Part #	Size Usage Range		Maximum Allowable Back Pressure PSI and Feet of Head		Required Inflation Pressure	Weight	Deflated Diameter	Deflated Length	Inflation Fittings	Eye Bolt Size & Quantity	Bypass Size	List Price
		Minimum Diameter	Maximum Diameter										
24"-60" FatBoy Plugster™ With Max-Guard™ (relief valve)	200-2460MG	21"	61.5"	9 PSI	20 FT	25 PSI	175 lbs	20.5"	95"	(1) (1/4" QD Nipple (removable)) (1) 1/2" NTP (F)	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	None	\$ 7,090.00
24"-60" FatBoy Plugster™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed	200-2460 MGMS	21"	61.5"	9 PSI	20 FT	25 PSI	240 lbs	21"	95"	(1) (1/4" QD Nipple (removable)) (1) 1/2" NTP (F)	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	None	\$ 8,990.00
24"-60" FatBoy Tester™ With Max-Guard™ (relief valve)	225-2460MG	21"	61.5"	9 PSI	20 FT	25 PSI	180 lbs	20.5"	95"	(1) (1/4" QD Nipple (removable)) (1) 1/2" NTP (F)	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	3/4" and 1/4" (f) NPT	\$ 7,490.00
24"-60" FatBoy Tester™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed	225-2460 MGMS	21"	61.5"	9 PSI	20 FT	25 PSI	245 lbs	21"	95"	(1) (1/4" QD Nipple (removable)) (1) 1/2" NTP (F)	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	3/4" and 1/4" (f) NPT	\$ 9,390.00
24"-60" FatBoy Guzzler™ With 4" Bypass and Max-Guard™ (relief valve)	250-2460MG	21"	61.5"	9 PSI	20 FT	25 PSI	200 lbs	20.5"	95"	(1) (1/4" QD Nipple (removable)) (1) 1/2" NTP (F)	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (m) NPT	\$ 8,250.00
24"-60" FatBoy Guzzler™ With 4" Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed	250-2460 MGMS	21"	61.5"	9 PSI	20 FT	25 PSI	265 lbs	21"	95"	(1) (1/4" QD Nipple (removable)) (1) 1/2" NTP (F)	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	4" (m) NPT	\$ 10,150.00
24"-60" FatBoy Guzzler™ With 6" Bypass and Max-Guard™ (relief valve)	276-2460MG	21"	61.5"	9 PSI	20 FT	25 PSI	215 lbs	20.5"	95"	(1) (1/4" QD Nipple (removable)) (1) 1/2" NTP (F)	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	6" (m) NPT	\$ 8,600.00
24"-60" FatBoy Guzzler™ With 6" Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed	276-2460 MGMS	21"	61.5"	9 PSI	20 FT	25 PSI	270 lbs	21"	95"	(1) (1/4" QD Nipple (removable)) (1) 1/2" NTP (F)	(2) 1/2" Eyebolts (2) 1/2" Optional Backside	6" (m) NPT	\$ 10,500.00
24"-60" Max-Sleeve™	600-2460	1/4"	N/A	N/A	N/A	N/A	65 lbs	21"	95"	N/A	N/A	N/A	\$ 1,725.00
24"-60" Max-Sleeve™ Installed on Matching Plug (includes Cable Harness Kit)	600-2460Si	1/4"	N/A	N/A	N/A	N/A	65 lbs	21"	95"	N/A	N/A	N/A	\$ 1,900.00
24"-48"/24"-60" Cable Harness Kit	605-2448	1/4"	N/A	N/A	N/A	N/A	1 lbs	21"	N/A	N/A	N/A	N/A	\$ 50.00