

Description	Part #	Size Usage Range		Maximum Allowable Back Pressure PSI and Feet of Head	Required Inflation Pressure	Weight	Deflated Diameter	Deflated Length	Inflation Fitting	Eye Bolt Size & Quantity	Bypass Size (connection)
		Minimum Diameter	Maximum Diameter								
3"-4" FatBoy Guzzler™ Aluminum Threaded Bypass with 1/4" Female NPT Connection	250-34	2.75" 70 mm	4.3" 109 mm	20 PSI 46 Ft	35 PSI	.75 LBS	2.65"	6.25"	1/8" Tank Valve (removable) and QD Nipple	(1) 1/4" Eyebolt Frontside	1/4" NPT (female) Threaded
4" - 6" FatBoy Guzzler™ Aluminum Threaded Bypass with 3/4" Female NPT Connection	250-46	3.75" 95 mm	6.4" 162 mm	17 PSI 39 Ft	45 PSI	2.25 lbs	3.5"	9"	1/8" Tank Valve (removable) and QD Nipple	(1) 1/4" Eyebolt Frontside	3/4" NPT (female) Threaded
6"-8" Max-Flow Guzzler™ with 4" OD Aluminum Bypass with Slip Fit Connection (no threads)	264-68	5.75" 150 mm	8.5" 215 mm	10 PSI 23 Ft	40 PSI	7.5 lbs	5.5"	14"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	4" (male) Tube (Slip-Fit) No Threads
6"-10" FatBoy Guzzler™ with 2" Threaded Aluminum Bypass with 2" Female NPT Connection	250-610	5.5" 140 mm	10.5" 266 mm	13 PSI 30 Ft	30 PSI	7 lbs	5.25"	17.5"	1/8" Tank Valve (removable) and QD Nipple	(1) 1/4" Eyebolt Frontside	2" NPT (female) Threaded
6"-10" Max-Guzzler™ with 4" Threaded Aluminum Bypass with 4" Male NPT Connection	274-610	5.75" 146 mm	10.5" 250 mm	10 PSI 23 Ft	35 PSI	13 lbs	5.6"	23"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	4" NPT (male) Threaded
8"-12" FatBoy Guzzler™ with 3" Threaded Aluminum Bypass with 3" Female NPT Connection	250-812	7" 177 mm	12.64" 321 mm	13 PSI 30 Ft	25 PSI	11.5 lbs	6.75"	19"	1/4" QD Nipple (removable)	(1) 3/8" Eyebolt Frontside	3" NPT (female) Threaded
8"-12" Max-Guzzler™ with 4" Threaded Aluminum Bypass with 4" Male NPT Connection	274-812	7" 177 mm	12.64" 321 mm	10 PSI 23 Ft	45 PSI	20 lbs	6.5"	26.5"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	4" NPT (male) Threaded
8-12" Max-Flow Guzzler™ with 4" Aluminum Tube Bypass with Slip Fit Connections (no threads)	264-812	7" 175 mm	12.5" 315 mm	10 PSI 23 Ft	40 PSI	10.5 lbs	5.5"	19"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	4" (male) Tube (Slip-Fit) No Threads
8"-12" Max-Guzzler™ with 6" Threaded Aluminum Bypass with 6" Male NPT Connection	276-812	7" 175 mm	12.64" 321 mm	10 PSI 23 Ft	35 PSI	20 lbs	7.5"	25"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	6" NPT (male) Threaded
8-12" Max-Flow Guzzler™ with 6" OD Aluminum Bypass with Slip Fit Connections (no threads)	266-812	7.75" 195 mm	12.50" 315 mm	10 PSI 23 Ft	40 PSI	14 lbs	7.25"	19"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	6" (male) Tube (Slip-Fit)
12"-18" FatBoy Guzzler™ with 4" Threaded Aluminum Bypass with 4" Male NPT Connection	274-1218	10.75" 300 mm	18.5" 470 mm	10 PSI 23 Ft	35 PSI	47 lbs	10.5"	32"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	4" NPT (male) Threaded
12"-18" FatBoy Guzzler™ with 4" Threaded Aluminum Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 4" Male NPT Connection	274-1218 MGMS	10.75" 300 mm	18.5" 470 mm	10 PSI 23 Ft	35 PSI	47 lbs	10.5"	32"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	4" NPT (male) Threaded
12"-18" Max-Guzzler™ with 6" Threaded Aluminum Bypass with 6" Male NPT Connection	276-1218	10" 254 mm	18.5" 470 mm	10 PSI 23 Ft	35 PSI	48 lbs	9.5"	30.75"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	6" NPT (male) Threaded
12"-18" FatBoy Guzzler™ with 6" Threaded Aluminum Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 6" Male NPT Connection	276-1218 MGMS	10" 254 mm	18.5" 470 mm	10 PSI 23 Ft	35 PSI	58 lbs	10"	30.75"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	6" NPT (male) Threaded
12"-18" FatBoy Guzzler™ with 8" Threaded Aluminum Bypass with 8" Male NPT Connection	278-1218	10" 254 mm	18.5" 470 mm	10 PSI 23 Ft	35 PSI	48 lbs	9.5"	31"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	8" NPT (male) Threaded (no cap)
12"-18" FatBoy Guzzler™ with 8" Threaded Aluminum Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 8" Male NPT Connection	278-1218 MGMS	10" 254 mm	18.5" 470 mm	10 PSI 23 Ft	35 PSI	58 lbs	10"	30.75"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	8" NPT (male) Threaded (no cap)
12"-24" Max-Guzzler™ with 4" Threaded Aluminum Bypass with 4" Male NPT Connection	274-1224	10" 254 mm	24.5" 622 mm	5 PSI 11.5 Ft	45 PSI	59 lbs	9.5"	42.5"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	4" NPT (male) Threaded
12"-24" FatBoy Guzzler™ with 4" Threaded Aluminum Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 4" Male NPT Connection	274-1224 MGMS	10" 254 mm	24.5" 622 mm	5 PSI 11.5 Ft	45 PSI	72 lbs	9.5"	42.5"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	4" NPT (male) Threaded
12"-24" Max-Guzzler™ with 6" Threaded Aluminum Bypass with 6" Male NPT Connection	276-1224	10" 254 mm	24.5" 622 mm	5 PSI 11.5 Ft	45 PSI	61 lbs	9.5"	42.5"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	6" NPT (male) Threaded
12"-24" FatBoy Guzzler™ with 6" Threaded Aluminum Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 6" Male NPT Connection	276-1224 MGMS	10" 254 mm	24.5" 622 mm	5 PSI 11.5 Ft	45 PSI	77 lbs	9.5"	42.5"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	6" NPT (male) Threaded
12"-24" Max-Guzzler™ with 8" Threaded Bypass with 8" Male NPT Connections (no PVC cap)	278-1224	10" 254 mm	24.5" 622 mm	5 PSI 11.5 Ft	45 PSI	63 lbs	9.5"	43"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	8" NPT (male) Threaded (no cap)
12"-24" FatBoy Guzzler™ with 8" Threaded Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 8" Male NPT Connections (no PVC cap)	278-1224 MGMS	10" 254 mm	24.5" 622 mm	5 PSI 11.5 Ft	45 PSI	77 lbs	9.5"	43"	1/4" QD Nipple (removable)	(1) 1/4" x 1-1/8" Galvanized Shackles Frontside	8" NPT (male) Threaded (no cap)
15"-30" FatBoy Guzzler™ with 4" Flexible Bypass and Max-Guard™ (relief valve) with 4" Male NPT Connection	250-1530MG	14" 355 mm	31.5" 775 mm	11 PSI 25 Ft	25 PSI	68 lbs	14"	58"	(1) 1/4" QD Nipple (removable) (1) 1/2" (Female) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	4" NPT (male) Threaded
15"-30" FatBoy Guzzler™ with 4" Flexible Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 4" Male NPT Connection	250-1530 MGMS	14.25" 362 mm	31.5" 775 mm	11 PSI 25 Ft	25 PSI	90 lbs	14"	58"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	4" NPT (male) Threaded
18"-36" FatBoy Guzzler™ with 4" Flexible Bypass and Max-Guard™ (relief valve) with 4" Male NPT Connection	250-1836MG	16.5" 419 mm	37.5" 950 mm	11 PSI 25 Ft	25 PSI	88 lbs	16"	65"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	4" NPT (male) Threaded
18"-36" FatBoy Guzzler™ with 4" Flexible Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 4" Male NPT Connection	250-1836 MGMS	17" 430 mm	37.5" 950 mm	11 PSI 25 Ft	25 PSI	118 lbs	16.5"	65"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	4" NPT (male) Threaded
24"-48" FatBoy Guzzler™ with 4" Flexible Bypass and Max-Guard™ (relief valve) with 4" Male NPT Connection	250-2448MG	22" 558 mm	49.5" 1,257 mm	11 PSI 25 Ft	25 PSI	140 lbs	21"	82"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	4" NPT (male) Threaded
24"-48" FatBoy Guzzler™ with 4" Flexible Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 4" Male NPT Connection	250-2448 MGMS	22" 558 mm	49.5" 1,257 mm	11 PSI 25 Ft	25 PSI	190 lbs	21"	82"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	4" NPT (male) Threaded
24"-48" FatBoy Guzzler™ with 6" Flexible Bypass and Max-Guard™ (relief valve) with 4" Male NPT Connection	276-2448MG	22" 558 mm	49.5" 1,257 mm	11 PSI 25 Ft	25 PSI	150 lbs	21"	82"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	6" NPT (male) Threaded
24"-48" FatBoy Guzzler™ with 6" Flexible Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 6" Male NPT Connection	276-2448 MGMS	22" 558 mm	49.5" 1,257 mm	11 PSI 25 Ft	25 PSI	200 lbs	21"	82"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	6" NPT (male) Threaded
24"-60" FatBoy Guzzler™ With 4" Flexible Bypass and Max-Guard™ (relief valve) with 4" Male NPT Connection	250-2460MG	21"	61.5" 1560 mm	9 PSI Ft	20	25 PSI	200 lbs	20.5"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	4" NPT (male) Threaded
24"-60" FatBoy Guzzler™ With 4" Flexible Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 4" Male NPT Connection	250-2460 MGMS	21"	61.5" 1560 mm	9 PSI Ft	20	25 PSI	265 lbs	21"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	4" NPT (male) Threaded
24"-60" FatBoy Guzzler™ With 6" Flexible Bypass and Max-Guard™ (relief valve) with 6" Male NPT Connection	276-2460MG	21"	61.5" 1560 mm	9 PSI Ft	20	25 PSI	215 lbs	20.5"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	6" NPT (male) Threaded
24"-60" FatBoy Guzzler™ With 6" Flexible Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with 6" Male NPT Connection	276-2460 MGMS	21"	61.5" 1560 mm	9 PSI Ft	20	25 PSI	270 lbs	21"	(1) 1/4" QD Nipple (removable) (1) 1/2" (F) NTP (plugged)	(2) 1/2" Eyebolt Frontside (2) 1/2" Eyebolt Optional Backside	6" NPT (male) Threaded