

Part #	Description	Usage Range	Unit OD	Bladder Inflation Pressure	Weight
555-2127	21"-27" Bladder-Max™ Manhole Vacuum Testing Unit with Cam-Lock® style connection	21" - 27.5"	20.75"	25 PSI	72 lbs
555-2832	28"-32" Bladder-Max™ Manhole Vacuum Testing Unit with Cam-Lock® style connection	28"-32"	27.75"	25 PSI	110 lbs
555-38	38" Flat-Max™ Manhole Vacuum Unit with Cam-Lock® stlye connection	18"-36"	38"	N/A	45 lbs
550-38	38" Flat-Max™ Manhole Vacuum Unit with Chicago (crowsfoot) style connection	18"-36"	38"	N/A	45 lbs
555-44	44" Flat-Max™ Manhole Vacuum Unit with Cam-Lock® style connection	18"-42"	44"	N/A	70 lbs
550-44	44" Flat-Max™ Manhole Vacuum Unit with Chicago (crowsfoot) style connection	18"-42"	44"	N/A	70 lbs
555-00	Max-Vac™ II Venturi Pump with Cam-Lock® style connection	N/A	N/A	N/A	10 lbs
550-00	Max-Vac™ II Venturi Pump with Chicago (crowsfoot) style connection	N/A	N/A	N/A	10 lbs
55-2127B	21"-27" Replacement Bladder	21" - 27.5"	20.75"	25 PSI	19 lbs
55-2832B	28"-32" Replacement Bladder	28"-32"	27.75"	25 PSI	33 lbs
37-001	0-60 PSI Liquid Filled Gauge (bladder inflation)	0-60 PSI	2.5"	N/A	.5 lbs
37-010	Rubber Gauge Guardian Bottom Mount 2.5" Dial	2.5"	4"	N/A	.5 lbs
37-012	Rubber Gauge Guardian Bottom Mount 4" Dial	4"	6"	N/A	.5 lbs
37-011	0-60 PSI Liquid Filled Gauge 2.5" Dial (bladder inflation) with Gauge Guardian Installed	0-60 PSI	2.5"	N/A	1 lbs
37-006	0-30HG Liquid Filled Vacuum Gauge	0-30 HG	4"	N/A	1 lbs
55-38F	1" Replacement Foam liner for 38" Flat-Max™ Plate (peal and stick)	38"	N/A	N/A	5 lbs
55-44F	1" Replacement Foam liner for 44" Flat-Max™ Plate (peal and stick)	44"	N/A	N/A	8 lbs