

Plug Technologies, Inc.

Specification Sheet



Image does not include the Max-sleeve

Part Number: 200-1218MGMS
Description: 12"-18" FatBoy Plugster™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed
Plug Body Material: Natural Rubber, Polyester Cord
Plug End Material: Natural Rubber, Polyester Cord
Cover Plate Material: 3/16" Zinc Plated Steel
Max-Sleeve Material: ¼" Natural Rubber
Max-Sleeve Eyelet Material: (4) on Each End, Natural Rubber and Polyester Cord
Required Inflation Pressure: 25 PSI
Maximum Test Pressure: 13 PSI
Max-Guard (relief valve): Brass Material
Plug Usage Range in Inches: Minimum Diameter 11" – Maximum Diameter 18.50"
Plug Usage Range in Metric: Minimum Diameter 300mm – Maximum Diameter 479mm
Temperature Rating: 125 Degrees Fahrenheit
Bypass Size: N\A
Weight: 35 lbs.
Deflated Diameter: 10.75"
Plug Length: 28"
Inflation Ports: Removable: ¼" QD Nipple
Eye Bolt(s) Quantity and Size: (1) (3/8") Frontside/Optional (1) 3/8" Backside Rev: 06/2021