



# Plug Technologies, Inc.

## Specification Sheet



Part Number: 200-1836MGMS

Description: 18"-36" FatBoy Plugster™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed

Plug Body Material: Natural Rubber, Polyester Cord

Plug End Material: Natural Rubber, Polyester Cord

Cover Plate Material: 3/16" Zinc Plated Steel

Max-Sleeve Material: 1/4" Natural rubber

Max-Sleeve Eyelet Material: (4) on Each End, Natural Rubber and Polyester Cord

Required Inflation Pressure: 25 PSI

Max-Guard (relief valve): Brass Material

Maximum Test Pressure: 11 PSI

Plug Usage Range in Inches: Minimum Diameter:17" - Maximum Diameter 37.5"

Plug Usage Range in Metric: Minimum Diameter 420mm - Maximum Diameter 950mm

Maximum Affluent Temperature: 125 Degrees Fahrenheit

Bypass Size: 3/4" NPT (female) (plugged) / 1/4" NPT (female)(plugged)

Weight: 120 LBS

Deflated Diameter: 16"

Plug Length: 60"

Inflation Port (s): Removable (1) 1/4" NPT and (1) 1/2" NPT

Eye Bolt(s) Quantity and Size: 2 (1/2") Frontside/Optional: 2 (1/2") Backside

Rev: 06/2021