



Plug Technologies, Inc.

Specification Sheet



Part Number: 200-2448MGMS

Description: 24"-48" FatBoy Plugster™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed

Plug Body Material: Natural Rubber, Polyester Cord

Plug End Material: Natural Rubber, Polyester Cord

Cover Plate Material: 3/16" Zinc Plated Steel

Max-Sleeve Material: ¼" Natural rubber

Max-Sleeve Eyelet Material: (4) on Each End, Natural Rubber and Polyester Cord

Required Inflation Pressure: 25 PSI

Max-Guard (relief valve): Brass Material

Maximum Test Pressure: 11 PSI

Plug Usage Range in Inches: Minimum Diameter 22" - Maximum Diameter 49.5"

Plug Usage Range in Metric: Minimum Diameter 610mm - Maximum Diameter 1220mm

Maximum Affluent Temperature: 125 Degrees Fahrenheit

Bypass Size: NA

Weight: 170 LBS

Deflated Diameter: 21"

Plug Length: 76

Inflation Port (s): Removable (1) ¼" NPT and (1) ½" NPT

Eye Bolt(s) Quantity and Size: 2 (½") Frontside/Optional: 2 (½") Backside

Plug Technologies, Inc. 11099 Lamont Ave NE Hanover, MN 55341

www.plugtechinc.com