



Plug Technologies, Inc.

Specification Sheet



Part Number: 200-2460MGMS

Description: 24"-60" FatBoy Plugster™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed

Plug Body Material: Natural Rubber, Polyester Cord

Plug End Material: Natural Rubber, Polyester Cord

Cover Plate Material: 1/4" Zinc Plated Steel

Max-Sleeve Material: 1/4" Natural rubber

Max-Sleeve Eyelet Material: (4) on Each End, Natural Rubber and Polyester Cord

Required Inflation Pressure: 25 PSI

Max-Guard (relief valve): Brass Material

Maximum Test Pressure: 9 PSI

Plug Usage Range in Inches: Minimum Diameter 22" - Maximum Diameter 61.5"

Plug Usage Range in Metric: Minimum Diameter 610mm - Maximum Diameter 1550mm

Maximum Affluent Temperature: 125 Degrees Fahrenheit

Bypass Size: NA

Weight: 240 LBS

Deflated Diameter: 20.5"

Plug Length: 95"

Inflation Port (s): Removable (1) 1/4" NPT and (1) 1/2" NPT

Eye Bolt(s) Quantity and Size: 2 (1/2") Frontside/Optional: 2 (1/2") Backside

Rev: 06/2021