



Plug Technologies, Inc.

Specification Sheet



Image shown without Max-Sleeve™

Part Number: 225-1218MS

Description: 12"-18" FatBoy Tester™ and Max-Sleeve™ Installed

Plug Body Material: Natural Rubber, Polyester Cord

Plug End Material: Natural Rubber, Polyester Cord

Cover Plate Material: 3/16" Zinc Plated Steel

Max-Sleeve Material: 1/4" Natural Rubber

Max-Sleeve Eyelet Material: (4) on Each End, Natural Rubber and Polyester Cord

Required Inflation Pressure: 25 PSI

Maximum Test Pressure: 13 PSI

Max-Guard (relief valve): NA

Plug Usage Range in Inches: Minimum Diameter 11" – Maximum Diameter 18.50"

Plug Usage Range in Metric: Minimum Diameter 300mm – Maximum Diameter 450mm

Temperature Rating: 125 Degrees Fahrenheit

Bypass Size: 3/4" NPT (female) and 1/4" NPT (female)

Weight: 42 lbs.

Deflated Diameter: 10.75"

Plug Length: 28"

Inflation Ports: Removable: 1/4" QD Nipple

Eye Bolt(s) Quantity and Size: (1) (3/8") Frontside/Optional (1) 3/8" Backside

Rev: 06/2021