



Plug Technologies, Inc.

Specification Sheet



Part Number: 225-1530MGMS

Description: 15"-30" FatBoy Tester™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed

Plug Body Material: Natural Rubber, Polyester Cord

Plug End Material: Natural Rubber, Polyester Cord

Cover Plate Material: 3/16" Zinc Plated Steel

Max-Sleeve Material: ¼" Natural Rubber

Max-Sleeve Eyelet Material: (4) on Each End, Natural Rubber and Polyester Cord

Required Inflation Pressure: 25 PSI

Maximum Test Pressure: 11 PSI

Max-Guard (relief valve): Brass Material

Plug Usage Range in Inches: Minimum Diameter 14" – Maximum Diameter 31.50"

Plug Usage Range in Metric: Minimum Diameter 375mm – Maximum Diameter 800mm

Temperature Rating: 125 Degrees Fahrenheit

Bypass Size: 3/4" NPT (female) and 1/4" NPT (female)

Weight: 72 lbs.

Deflated Diameter: 13.75"

Plug Length: 50"

Inflation Ports: Removable: (1) 1/4" QD Nipple (removable)/(1) 1/2" (F) NTP (plugged)

Eye Bolt(s) Quantity and Size: (2) 1/2" Eyebolt Frontside/(2) Optional 1/2" Backside

Rev: 06/2021