



# Plug Technologies, Inc.

## Specification Sheet



Part Number: 225-2448MG

Description: 24"-48" FatBoy Tester™ With Max-Guard™ (relief valve)

Plug Body Material: Natural Rubber, Polyester Cord

Plug End Material: Natural Rubber, Polyester Cord

Cover Plate Material: 3/16" Zinc Plated Steel

Max-Sleeve Material: NA

Max-Sleeve Eyelet Material: NA

Required Inflation Pressure: 25 PSI

Maximum Test Pressure: 11 PSI

Max-Guard (relief valve): Brass Material

Plug Usage Range in Inches: Minimum Diameter 22" – Maximum Diameter 49.5"

Plug Usage Range in Metric: Minimum Diameter 610mm – Maximum Diameter 1250mm

Temperature Rating: 125 Degrees Fahrenheit

Bypass Size: 3/4" NPT (female) (plugged) / 1/4" NPT (female)(plugged)

Weight: 120 lbs.

Deflated Diameter: 21"

Plug Length: 76"

Inflation Ports: Removable: (1) 1/4" QD Nipple (removable) / (1) 1/2" (F) NTP (plugged)

Eye Bolt(s) Quantity and Size: (2) 1/2" Eyebolt Frontside / (2) Optional 1/2" Backside

Rev: 06/2021