



# Plug Technologies, Inc.

## Specification Sheet



Part Number: 225-2460MGMS

Description: 24"-60" FatBoy Tester™ With Max-Guard™ (relief valve) and Max-Sleeve™ Installed

Plug Body Material: Natural Rubber, Polyester Cord

Plug End Material: Natural Rubber, Polyester Cord

Cover Plate Material: 1/4" Zinc Plated Steel

Max-Sleeve Material: 1/4" Natural Rubber

Max-Sleeve Eyelet Material: (4) on Each End, Natural Rubber and Polyester Cord

Required Inflation Pressure: 25 PSI

Maximum Test Pressure: 9 PSI

Max-Guard (relief valve): Brass Material

Plug Usage Range in Inches: Minimum Diameter 22" – Maximum Diameter 61.5"

Plug Usage Range in Metric: Minimum Diameter 600mm – Maximum Diameter 1560mm

Temperature Rating: 125 Degrees Fahrenheit

Bypass Size: Flexible 3/4" NPT (female) (plugged) / 1/4" NPT (female)(plugged)

Weight: 245 lbs.

Deflated Diameter: 21"

Plug Length: 95"

Inflation Ports: Removable: (1) 1/4" QD Nipple (removable) / (1) 1/2" (F) NTP (plugged)

Eye Bolt(s) Quantity and Size: (2) 1/2" Eyebolt Frontside / (2) Optional 1/2" Backside

Rev: 06/2021