



# Plug Technologies, Inc.

## Specification Sheet



Image shown with Max-Sleeve™

Part Number: 250-1836MG

Description: 18"-36" FatBoy Guzzler™ with 4" Flexible Bypass and Max-Guard™ (relief valve) with 4" Male NPT Connection

Plug Body Material: Natural Rubber, Polyester Cord

Plug End Material: Natural Rubber, Polyester Cord

Cover Plate Material: 3/16" Zinc Plated Steel

Max-Sleeve Material: NA

Max-Sleeve Eyelet Material: NA

Required Inflation Pressure: 25 PSI

Max-Guard (relief valve): Brass Material

Maximum Test Pressure: 11 PSI

Plug Usage Range in Inches: Minimum Diameter 17" - Maximum Diameter 37.5"

Plug Usage Range in Metric: Minimum Diameter 419mm - Maximum Diameter 950mm

Maximum Affluent Temperature: 125 Degrees Fahrenheit

Bypass Size: 4" Flexible Hose with 4" NPT (male) Threaded Connection

Weight: 88 LBS

Deflated Diameter: 16"

Plug Length: 60"

Inflation Port (s): Removable (1) ¼" NPT and (1) ½" NPT Eye Bolt(s) Quantity and Size: 2 (½") Frontside/Optional: 2 (½") Backside

Rev: 06/2021