



Plug Technologies, Inc.

Specification Sheet



Part Number: 250-2448MG

Description: 24"-48" FatBoy Guzzler™ with 4" Flexible Bypass and Max-Guard™ (relief valve) with 4" Male NPT Connection

Plug Body Material: Natural Rubber, Polyester Cord

Plug End Material: Natural Rubber, Polyester Cord

Cover Plate Material: 3/16" Zinc Plated Steel

Max-Sleeve Material: ¼" Natural rubber

Max-Sleeve Eyelet Material: (4) on Each End, Natural Rubber and Polyester Cord

Required Inflation Pressure: 25 PSI

Max-Guard (relief valve): Brass Material

Maximum Test Pressure: 11 PSI

Plug Usage Range in Inches: Minimum Diameter 22" - Maximum Diameter 49.5"

Plug Usage Range in Metric: Minimum Diameter 558mm - Maximum Diameter 1257mm

Maximum Affluent Temperature: 125 Degrees Fahrenheit

Bypass Size: 4" Flexible Hose with 4" NPT (male) Threaded Connection

Weight: 140 LBS

Deflated Diameter: 21"

Plug Length: 82"

Inflation Port (s): Removable (1) ¼" NPT and (1) ½" NPT

Eye Bolt(s) Quantity and Size: 2 (½") Frontside/Optional: 2 (½") Backside

Rev: 06/2021