



Plug Technologies, Inc.

Specification Sheet



Image Shown with Max-Sleeve Installed

Part Number: 250-2460MG

Description: 24"-60" FatBoy Guzzler™ with 4" Flexible Bypass and Max-Guard™ (relief valve) with 4" Male NPT Connection

Plug Body Material: Natural Rubber, Polyester Cord

Plug End Material: Natural Rubber, Polyester Cord

Cover Plate Material: ¼" Zinc Plated Steel

Max-Sleeve Material: NA

Max-Sleeve Eyelet Material: NA

Required Inflation Pressure: 25 PSI

Max-Guard (relief valve): Brass Material

Maximum Test Pressure: 9 PSI

Plug Usage Range in Inches: Minimum Diameter 21" - Maximum Diameter 61.5"

Plug Usage Range in Metric: Minimum Diameter 558mm - Maximum Diameter 1560mm

Maximum Affluent Temperature: 125 Degrees Fahrenheit

Bypass Size: 4" Flexible Hose with 4" NPT (male) Threaded Connection

Weight: 200 LBS

Deflated Diameter: 21"

Plug Length: 95"

Inflation Port (s): Removable (1) ¼" NPT and (1) ½" NPT

Eye Bolt(s) Quantity and Size: 2 (½") Frontside/Optional: 2 (½") Backside

Rev: 06/2021