



Plug Technologies, Inc.

Specification Sheet



Image of 274-1224MGMS (no cap included for 8" bypass)

Part Number: 278-1224MGMS

Description: 12"-24" FatBoy Guzzler™ with 8" Threaded Aluminum Bypass and Max-Guard™ (relief valve) and Max-Sleeve™ Installed with " Male NPT Connection

Plug Material: Body & Ends - Natural Rubber, Polyester Cord

Plug End Material: Body & Ends - Natural Rubber, Polyester Cord

Required Inflation Pressure: 45 PSI

Max-Sleeve Material: ¼" Natural Rubber

Maximum Test Pressure: 5 PSI

Max-Guard (relief valve): Brass Material

Plug Usage Range in Inches: 10" – 24.5"

Plug Usage Range in Metric: 254mm – 622mm.

Temperature Rating: 125 Degrees Fahrenheit

Bypass Size: Rigid Aluminum Bypass with Threaded 8" Male NPT Connection (Cap not included)

Weight: 77 lbs

Deflated Diameter: 9.5"

Plug Length: 42.5"

Inflation Ports: Removable ¼" QD Nipple

Eye Bolt(s) Quantity and Size: (1) 1/4" x 1-1/8" Galvanized Shackles Frontside

Rev: 06/2021